

Lobby Entrance Matting

100% Polypropylene patterned fibre bonded tiles and sheet with superb heavy contract qualities such as spike resistance.

Construction

	Tile	Sheet
Fibre Content	100% Polypropylene	100% Polypropylene
Backing	Bitumen	Gel Foam
Pile Weight	1500g/m ²	1500g/m ²
Total Weight	5820g/m ²	2185g/m ²
Pile Height	4.50mm	4.50mm
Total Height	11.00mm	10.00mm
Tile Size/Width	50cm x 50cm	2m Wide
M ² per box/Roll length	3m ²	25lm

All weights and thickness measurements ± 10%. All other dimensions ±1%

Performance

Classification	ISO 10874	Class 32
Static	EN 6356	<2.0kV
Acoustic Impact Noise	ISO 717-2	24dB
Castor Chair (tile)	EN 985	Occasional Use
Castor Chair (sheet)	EN 985	Continuous Use
Reaction to Fire	EN 13501-1	Efl
Colour Fastness to rubbing	ISO 105 X12	4 - Good
Use on Stairs (tile)	ISO 12951	Occasional Use
Use on Stairs (sheet)	ISO 12951	Continuous Use

Installation



These products must be fitted in accordance with the CFS fitting instructions, which are available on request.

Recommended adhesives

Tile: F Ball F41 tackifier & Mapei ECO Tack

Sheet: F Ball F3, Mapei Ultrabond Eco Fix (Normal use) & Mapei Ultrabond Eco VS90 Plus (High Temperature use)

SAMPLING SERVICE

If you require a large sample, please list the product name and colour followed by your address details and email to: samples@cfsflooring.co.uk

Approved CFS Stockists

Carpet & Flooring Branches Nationwide:

Glasgow T: 0141 218 3160 | **Gateshead** T: 0191 482 8730 | **Manchester** T: 0161 786 6800

Birmingham T: 0121 421 9131 | **Cambridge** T: 01954 782224 | **Cardiff** T: 029 2099 0460

Bristol T: 0117 316 0555 | **London, Camberley** T: 01276 672100 | **London, Bow** T: 020 8620 0090

Kent T: 01634 668668



Sheet only



Sheet only

