

New Typhoon

A robust fine rib fibre bonded range used on a regular basis by flooring contractors. Fibre bonded carpets are simple to install, hard wearing, high performance and easy maintenance making them the ideal flooring choice for heavy traffic areas.

Construction

	Tile	Sheet
Fibre Content	80% Polypropylene, 20% Nylon	80% Polypropylene, 20% Nylon
Backing	Bitumen	Resin
Pile Weight	900g/m ²	900g/m ²
Pile Height	3.50mm	3.50mm
Total Weight	4100g/m ²	1100g/m ²
Total Height	8.50mm	5.00mm
Tile Size/Roll Size	50cm x 50cm*	2m Wide*
M ² per box/Roll length	5m ²	30lm

All weights and thickness measurements ± 10%. All other dimensions ±1%

*Available to special order 60cm x 60cm and 4m wide broadloom (subject to minimum order quantity).



Performance

Warranty	10 Years	
Static	Stroll Test ISO 6356	Pass
Electrical Resistance	IBM/ICL	
Flammability	HotMetal Nut: BS 4790	Assessed to BS 5287
Dimensional Stability	BS 4682 (Tile only)	
Castor Chair	BS EN 985	
Underfloor Heating	Up to 27°C	
Colour Fastness	To light	EN ISO 105 B02
	To water	EN ISO 105 E01
	To wet and dry rubbing	EN ISO 105 X12

Installation



These products must be fitted in accordance with the CFS fitting instructions, which are available on our website www.cfscarpets.co.uk

Recommended adhesives

Tiles: F Ball F41 tackifier, Laybond 79 or Mapei ECO Tack
Sheet: F Ball F3 / 52, Laybond 73 Multicryl / 47 CV / 48 Extra

SAMPLING SERVICE

If you require a large sample, please list the product name and colour followed by your address details and email to: samples@cfscarpets.co.uk

Approved CFS Stockists

Carpet & Flooring Branches Nationwide:

Glasgow T: 0141 427 8456 | **Gateshead** T: 0191 482 7373 | **Manchester** T: 0161 786 6800

Birmingham T: 0121 421 9131 | **Cambridge** T: 01954 782 224 | **Cardiff** T: 029 2099 0460

Bristol T: 0117 316 0555 | **London, Camberley** T: 01276 672100 | **London, Bow** T: 020 8525 5691

London, Colindale T: 020 7127 6770 | **Chatham, Kent** T: 01634 668 668

