

QUALITY
ORDER CODE

DATE: **12/02/2018**
REPLACES: 4/01/2017

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (± 15%) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

PEMBRIDGE HEATHERS SB
PBH

± 400 & 500
COLLECTION
1/10" TWIST

SOLUTION DYED

PP

WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 810
± 1.780

± 6,0
± 8,5
± 157.600
± 39,40
± 40,00

±
±

± 26
PILE IN

✓
✓

✓

NO SHOCK

Cl. 22
Domestic General/Medium



LC2 

Efl 

Heavy domestic / General non-domestic

QUALITY

DIMENSIONAL STABILITY

EN 986

≤

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

± 20



SOUND ABSORPTION

(±)

α_s

ISO 354 - 125 Hz

±

(±)

250Hz

±

(±)

500Hz

±

(±)

1000Hz

±

(±)

2000Hz

±

(±)

4000Hz

±

SOUND ABSORPTION

(±)

α_w

EN ISO 11654

±

THERMAL RETENTION

(±) m²/KW

ISO 8302

± 0,16

TOG rating

(±)

± 1,6

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

≤

SURFACE RESISTANCE RoT

(±) ohm

ISO 10965

≤

SURFACE RESISTANCE RdT

(±) ohm

ISO 10965

≤

LIGHTFASTNESS

ISO 105-B02

≥ 5

RUBBINGFASTNESS DRY

ISO 105 X12

≥ 3-4

RUBBINGFASTNESS WET

ISO 105 X12

≥ 3

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01

≥ 3-4

WATERFASTNESS STAINING

ISO 105-E01

≥ 2-3

LABEL CE

17 **CE**
EN 14041
DOP 1038-124277



LANO NV - Venetiëlaan 33
B-8530 HARELBEKE
Floor carpets to use in
buildings

RECOMMENDED INSTALLATION

ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

COLOURS

AVAILABLE FROM

AVAILABLE FROM

<u>SB 400</u>	PBH	<u>SB 500</u>
180	RUM	180
220	ACORN	220
230	FLAX	230
250	MAGNOLIA	250
260	CAMEL	260
420	CORNSTALK	420
452	SAND 2	452
810	CHARCOAL	810
830	ASH	830
840	MOONSHINE	840
860	GRANITE	860
870	SILVER	870
873	DOLPHIN	873
880	PEARL	880

<u>SB 400</u>	PBH	<u>SB 500</u>
---------------	------------	---------------



WE RESERVE THE RIGHT TO
ALTER TECHNICAL SPECIFICATIONS
WITHOUT PRIOR NOTICE

(14)

(14)