

QUALITY  
ORDER CODE

WIDTH (±) cm  
TYPE  
GAUGE AND TYPE  
TEXTURING  
DYEING/PRINT METHOD

PILE COMPOSITION  
FIBRE BRAND  
MOTHPROOF

PRIMARY BACKING  
SECONDARY BACKING

PILE WEIGHT (±) gr/m<sup>2</sup>  
TOTAL WEIGHT (±) gr/m<sup>2</sup>

EFFECTIVE PILE HEIGHT (±) mm  
TOTAL HEIGHT (±) mm  
NUMBER OF KNOTS (±) m<sup>2</sup>  
STITCHES OVER WIDTH (±) / 10 cm  
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm  
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m  
PILE IN/OUT

DATE: 3/02/2020  
REPLACES: 22/01/2020

**SERENADE RUSTIQUE SMB**  
**SRU**

± 400 & 500  
COLLECTION  
1/8" SAXONY

SOLUTION DYED

PP

WOVEN

SMART BACK

± 2.040  
± 2.890

± 13,5  
± 16,0  
± 122.850  
± 31,50  
± 39,00

±  
±

± 25  
PILE IN

**LANO CLASSIFICATION**

BEDROOM  
LIVING ROOM  
OFFICE  
CASTOR ROLLCHAIRS DOMESTIC USE  
CASTOR ROLLCHAIRS PROFESSIONAL USE  
STAIRS DOMESTIC USE  
STAIRS PROFESSIONAL USE  
ELECTROSTATIC BEHAVIOUR  
UNDERFLOOR HEATING  
BATH ROOM  
NON-FRAY  
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER  
DIBT

UPEC n°  
CLASSIFICATION

HQE  
EN 1307

✓  
✓

NO SHOCK

Cl. 21  
Domestic Moderate/Light



LC5



Efl



Heavy domestic / General non-domestic

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION  
CLASSIFICATION BS7131

QUALITY

IMPACT SOUND INSULATION	(±) dB	ISO 140/8
THERMAL RETENTION	(±) m²/KW	ISO 8302
TOG rating	(±)	
PERMANENTLY ANTISTATIC	(±) volt	ISO 6356
LIGHTFASTNESS		ISO 105-B02
RUBBINGFASTNESS DRY		ISO 105 X12
RUBBINGFASTNESS WET		ISO 105 X12
WATERFASTNESS CHANGE IN COLOUR		ISO 105-E01
WATERFASTNESS STAINING		ISO 105-E01

**SERENADE RUSTIQUE SMB**

± 25



± 0,21



± 2,1

≤


≥ 5

≥ 3-4

≥ 3

≥ 3-4

≥ 2-3



ALL-OVER STICK DOWN  
WITH EC1 APPROVED ADHESIVE

LABEL CE

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

<u>SMB 400</u>	<u>SRU</u>	<u>SMB 500</u>
0230	FLAX	0230
0233	CARAMEL	0233
0253	HARVEST	0253
0263	CAMEL	0263
0273	LIMESTONE	0273
0423	CORNSTALK	0423
0433	ELMWOOD	0433
0823	RAINSHOWER	0823
0830	ASH	0830
0843	FOSSIL	0843
0850	MOONBEAM	0850
0860	GRANITE	0860

<u>SMB 400</u>	<u>SRU</u>	<u>SMB 500</u>



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE

(12)

(12)